1710W LED Lunar Lite®

Total LED Efficacy of 393,300 Lumens from a SINGLE light head

"WE LEAVE OUR COMPETITORS IN THE DARK"











www.LunarLighting.com

1710W LED Lunar Lite®

360° Anti-Glare Portable LED Light

Fully Directional lighting; 5x independent light segments of 72° per segment

Features**

- Dimmable
- Flicker Free
- LEDS rated for 50,000hrs
- Even and Uniform 360° Lighting
- Polymer Diffuser Durable & Tough
- Operating Temp range -40°F to 185°F
- Daylight color temperature 5000°Kelvin
- Adjustable from Visible light to Infrared light (Optional)
- Adjustable Wattages 342W 684W 1026W 1368W 1710W
- LED efficacy is 230 lm/W. 1710W LED efficacy is 393,300 lumens
- Light head Dimensions: 22 inches H x 17 inches D. Weight: 30lbs
- Input Voltage Options: 12VDC, 24VDC, 48VDC AND 90VAC to 305VAC
- Area lit approximately 6011sq. yds at 4.5yds height and min lux of 1
- HEAVY Duty Impact Resistant road-case for transportation and storage
- Typical Amperage draw is 15 Amps @ 110V for 1710W; 3 Amps for 342W
- Total Luminous Flux of 266,266 lumens after diffuser and driver reductions
- State of the Art LEDs which have Extreme Stability and high Thermal ability
- Innovative LED Thermal Management System with PURE Aluminium heat sink
- Can be Retrofitted to conventional lighting towers, poles, plant and machinery
 - ** Features and Figures may be subject to change at any time without notice © Lunar Lighting Innovations LLC 2024
- * Anti Glare properties are dependent upon dimmer switch settings.





